

Aluminium steel transition joints



| THICKNESS (MM) | LENGTH (MM) | WIDTH MIN - MAX (MM) | COMPOSITION | |
|----------------|-------------|----------------------|---------------------------------|---------|
| 19 | 3800 | 14 - 1350 | Aluminium alloy 5083 | 4,0 mm |
| | | | Aluminium 1050A | 5,0 mm |
| | | | Steel ASTM A516 Grade 55 | 10,0 mm |
| 28 | 3800 | 14 - 1350 | Aluminium alloy 5083 | 10,0 mm |
| | | | Aluminium 1050A | 3,0 mm |
| | | | Shipbuilding steel ASTM Grade D | 15,0 mm |
| 34,5 | 3800 | 14 - 1350 | Aluminium alloy 5086 | 6,0 mm |
| | | | Aluminium 1050A | 9,5 mm |
| | | | Steel ASTM A516 Grade 55 | 19,0 mm |
| 31,5 | 2750 | 14 - 1060 | Aluminium alloy 3003 | 10,0 mm |
| | | | Titanium ASTM B265 Grade 1 | 1,5 mm |
| | | | Stainless steel AISI 316L | 20,0 mm |
| 33,4 | 2750 | 14 - 1060 | Aluminium alloy 3003 | 12,9 mm |
| | | | Titanium ASTM B265 Grade 1 | 1,5 mm |
| | | | Steel ASTM A516 Grade 55 | 19,0 mm |